

Convert your wood burning fireplace to gas, for a new standard of warmth, beauty, safety and convenience.

MODEL FUEL INPUT LOW OUTPUT EFFICIENCY FE (P.4.1-02) IDV33N / IDV36N NATURAL 31,000 / 34,250 BTU 20,900 / 24,000 BTU 23,250 / 25,688 BTU 75%

57.4% / 58.4%

IDV33LP / IDV36LP PROPANE 28,500 / 30,000 BTU 23,100 / 22,840 BTU 21,375 / 22,500 BTU 75% 57.9% / 59.9%

STANDARD FEATURES*

- Dual Burner with glowing embers
- Millivolt valve system allows operation during power failure with Hi-Low heat and flame adjustment
- Matchless Piezo Ignition
- Decorative Ash Bed
- Ceramic Glass
- On/Off Rocker switch
- Heat activated blower with variable speed control
- Bedroom and bed sitting room approval
- Mobile home, bedroom and bed sitting room approval

OPTIONAL FEATURES*

Log Set – Fibre Split Oak

Glass Tray with Bronze Glass

Designer Clean View Kit – Black, Pewter, Copper Vein Surrounds for Clean View – Black, Copper Vein and Pewter Surround Picture Frame for Clean View – Black

Louver Kit – Grills available in Black, Classic Series Black with Antique, Chrome, or Polished Brass accents

Surrounds for Louver Kit - Black

Porcelain Reflective Liners

Brick Liner – Classic – (IDV33), Traditional or Herringbone – (IDV36)
Wall Mount Thermostat – Standard On/Off or Programmable
Remote Control – On/Off, Thermostat, or Modulating Hi/Lo
with Thermostat

Overlay Arch Doors – Deluxe, Top Half, Double Arch and Double Door

Designer Doors – Arch or Straight Doors with optional Antique, Chrome or Polished Brass trims

MINIMUM FIREPLACE OPENING

	WIDTH	HEIGHT	DEPTH
IDV33 IDV36		21 ³ / ₈ " 25 ⁵ / ₈ "	,

MINIMUM UNIT COVERAGE

IDV33	WIDTH	HEIGHT	IDV36	WIDTH	HEIGHT
IDV33 (Louvers) IDV33 (Clean View*)	34 ½" 32 ¾"	= . , ,	IDV36 (Louvers) IDV36 (Clean View*)	39" 37 1/4"	28 ³ / ₄ " 27"

*Back Frame Dimension of Clean View Kit

LOUVER KIT AND SURROUND SIZES

IDV33	WIDTH	HEIGHT	IDV36	WIDTH	HEIGHT
133LK (Louver Kit) 133S3426B (Surround) 133S4028B (Surround) 133S4430B (Surround) 133S4535B (Surround)	34 ½" 40"	24 ³ / ₈ " 27" 28 ³ / ₄ " 31 ³ / ₈ " 35"	136LK (Louver Kit) 136S3931B 136S4432B 136S4736B	39" 39" 44" 47"	28 ³ / ₄ " 32 ³ / ₈ " 33 ¹ / ₈ " 36"

CLEAN VIEW AND SURROUND SIZES

IDV33	WIDTH	HEIGHT	IDV36	WIDTH	HEIGHT
I33CV (Clean View) I33SPF1	35 %" 39 %"	2 1 /-	I36CV (Clean View) I36SS1	40" 43 ½"	28 ½" 30 ¼"
I33SSI	39 ¾"	26"			



Unit illustrated is a IDV36N Direct Vent Insert – NG, 136LK Louver Kit, LOGF36 Log Set – Fibre Spilt Oak, IDV36GBL Grill Kit – Black, IDV36RLT Refractory Brick Liner – Traditional



Unit illustrated is a IDV33LP Direct Vent Fireplace Insert – Propane, LOGF35 Split Fiber Oak Log Set, I33CVCV Clean View Kit – Copper Vein, I33SS1CV Surround for Clean View – Copper Vein, IDV33RL Refractory Brick Liner.



Unit illustrated is a IDV33LP Direct Vent Fireplace Insert – Propane, LOGF35 Split Fiber Oak Log Set – I33CVPW Clean View Kit – Pewter, I33SS1PW Surround for Clean View – Pewter, IDV33RL Refractory Brick Liner.



Intertek 4000720 Kingsman Fireplaces, maintains a program of continuous testing, refinement and improvements of all its products. Some aspect of units shown here may be changed at any time without notice or obligation. Certification: The models IDV33 and IDV36 are certified for Canada/USA as a Vented Gas Fireplace Heater ANSI 221.88-2009, CSA 2.33-2009, CSA 2.17-M91.

*Components may have to be ordered separately to create a complete unit Discuss with your local Kingsman dealer for clarification.



2340 Logan Avenue Winnipeg, Manitoba, Canada R2R 2V3 Phone: (204) 632-1962 Fax: (204) 632-1960 www.kingsmanfireplaces.com